
# Airtac

## 3F, 3FM Series



## Symbol


Without lock

With lock

## ■ Product feature

- 1. Direct acting and normally closed type.
- 2. The 3F series has aluminum foot pedal and 3FM series has plastic foot pedal, in direct acting type, horizontal and compact structure.
- 3. If the duration of direction-change is long, the valves with lock may be
- 4. The clamping framework is steady and reliable that it is easy and quick to unlock. However, with the limitation of the dimension of structure, it can not bear frequent strong impact.

#### ■ Inner structure



# Note: 🔥


Note:Lockable type should be added grease periodically to ensure the machine can work regularly

## Specification

Model	3 FM210-M5	3F210-06	3FM210-06	3F210-08	3FM210-08
Fluid	Air (to be filtered by 40 μm filter element)				
Operating	Acting type controlled by foot normally closed				
Port size①	M5	1/8"	1/4"	1/8"	1/4"
Valve type	3/2 Way				
Pressure range	0~0.8MPa(0~114psi)				
Proof pressure	1.5MPa(215psi)				
Temperature	-20~70℃				
Material body	3FM:Plastic; 3F:Aluminum alloy				
Lubrication	Not required				

1) PT thread, NPT thread and G thread are available.

### Ordering code



### Dimensions

